Data sheet for three-phase Squirrel-Cage-Motors Innomotics

Motor type : 1CV3205A **INNOMOTICS SD - 200 L - IM B3 - 2p**

Client order no.	Item-No.	Offer no.
Order no.	**Consignment no.**	**Project**

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η 3) 4/4	η 3) 3/4	η 3) 2/4	cosφ 3) 4/4	cosφ 3) 3/4	cosφ 3) 2/4	I_A/I_N I_I/I_N	M_A/M_N T_I/T_N	M_K/M_N T_B/T_N	IE-CL
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	37.00	-/-	65.00	2955	120.0	93.7	94.2	94.0	0.88	0.85	0.78	7.1	2.5	3.2	IE3
690	Y	50	37.00	-/-	37.50	2955	120.0	93.7	94.2	94.0	0.88	0.85	0.78	7.1	2.5	3.2	IE3
460	Δ	60	41.50	-/-	63.00	3555	111.0	93.0	93.3	92.9	0.89	0.87	0.80	7.1	2.5	3.2	IE2
460	Δ	60	37.00	-/-	57.00	3560	99.0	93.0	93.1	92.3	0.88	0.85	0.77	7.6	2.7	3.3	IE3

IM B3 / IM 1001		FS 200 L		IP55	UKCA	IEC/EN 60034	IEC, DIN, ISO, VDE, EN			

Environmental conditions : -20 °C - +40 °C / 1000 m	Locked rotor time (hot / cold) : 27.70 s | 46.80 s

Mechanical data

Sound level (SPL / SWL) at 50Hz|60Hz	67.0 / 80.0 dB(A) 2) 3)	77.0 / 84.0 dB(A) 2) 3)
Moment of inertia	0.1580 kg m²	
Bearing DE | NDE	6212 2Z C3	6212 2Z C3
Bearing lifetime		
L_{10mh} $F_{Rad\ min}$ for coupling operation 50|60Hz 1)	40000 h	32000 h
Regreasing device	Without	
Grease nipple	-/-	
Type of bearing	Locating bearing NDE	
Condensate drainage holes	With (standard)	
External earthing terminal	With (standard)	

Vibration severity grade	A
Thermal class	F
Duty type	S1
Direction of rotation	bidirectional
Frame material	cast iron
Net weight of the motor (IM B3)	245 kg
Coating (paint finish)	Standard paint finish C2
Color, paint shade	RAL7030
Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Method of cooling	IC411 - self ventilated, surface cooled
Carbon footprint (without options)	987kg

Terminal box

Terminal box position	top
Material of terminal box	cast iron
Type of terminal box	TB1 L01
Contact screw thread	6xM6
Max. cross-sectional area	25.0 mm²

Main cable entry	2xM50x1.5
Main cable gland	2 plugs
Auxiliary cable entry	1xM20x1.5
Auxiliary cable gland	1 plug

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department	Technical reference	Created by	Approved by	*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.*	Link documents
IN LV		IPC			

INNOMOTICS

Document type	Document status
Technical data sheet	Released
Document title	**Document number**
1LE1503-2AA53-4AB4	TDS-260417-111457

Restricted	Revision	Creation date	Language	Page
© Innomotics 2026	AA	2026-04-17	en	1/1