

Accessories

Programming accessories

Handheld Programming Tool Z-PA-EI-H



Features

- Battery operated stand-alone solution
- Intuitive, fully menu-driven programming
- Four user-assigned buttons for simple and quick programming
- Memory of several encoder configurations
- Backlit display
- LED status indicator
- Encoder diagnostic functions

Part number

11120657 Handheld Programming Tool Z-PA-EI-H

Note: Please order connection cable (see accessories).

Suitable for

EIL580P, HS35P, ITD2PH00.2

Accessories

Connectors and cables

11119280	Connection cable connector M12 / connector D-SUB, 0.2 m
11119720	Connection cable connector M12 / connector D-SUB, 1 m
11119257	Connection cable connector M23 / connector D-SUB, 0.2 m (S2BG12/K4SG9)
11119723	Connection cable connector M23 / connector D-SUB, 1 m (S2BG12/K4SG9)
11077210	Connection cable HS35P with connector MIL, 10-pin / connector D-SUB, 0.5 m
11077212	Connection cable HS35P with connector MIL, 7-pin / connector D-SUB, 0.5 m
11072169	Connection cable with FCI, 8-pin / wire end sleeves (UL/CSA), 1 m
11079111	Connection cable with FCI, 8-pin / D-SUB, 9-pin, 1 m
11135730	Connection cable connector M12 / connector D-SUB, 1 m - Option 3232

Technical data

Voltage supply	2.6 - 3.2 VDC
Operating temperature	+10...+60 °C
Storage temperature	-20...+80 °C
Connection	Connector D-SUB, 9-pin, female Cable terminals
Battery	2x AA (included in the delivery)
Weight approx.	135 g
Protection DIN EN 60529	IP 40

Terminal assignment

Connector D-SUB	Assignment	Cable terminal
Pin 1	Encoder A+ (A)	Terminal 3
Pin 2	NC	–
Pin 3	NC	–
Pin 4	Encoder UB (+Vs)	Terminal 1
Pin 5	Encoder GND (0 V)	Terminal 2
Pin 6	NC	–
Pin 7	NC	–
Pin 8	NC	–
Pin 9	NC	–

