



NOTE: -  
 TERMINAL BOX CAN BE MOUNTED (LEFT OR RIGHT) BY REFITTING FEET AND LIFTING LUGS 90° IN APPROPRIATE DIRECTIONS. CABLE ENTRY CAN BE SUPPLIED IN ANY ONE OF FOUR POSITIONS AT 90° INTERVALS.

NOTE!  
 2.5 ENDPLAY WILL BE PROVIDED FOR ENDTHRUST PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR INTENTION TO USE RIGID COUPLINGS AND DRIVEN MACHINES WITHOUT ENDPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT MOUNTED METRIC A.C. MOTOR. TOTALLY ENCLOSED FAN VENTILATED.  
 FRAME SIZE: W-DF280M (4 POLE UP.)

SCALE	1:8	DATE
DRAWN	B.J.T	19.2.93
CHECKED	B.J.T	19.2.93
APPROVED	I.J.W	19.2.93

CUSTOMER			
ORDER No.			
PART No.			
OUR ORDER No.			
FRAME SIZE			
KW.	RPM.		
Hz	PHASE		
VOLTS	POLES		
BRGS.	DE.	DE.	NDE.
MOTOR NETT WT.	Kg.		
SPECIAL REMARKS			

ALL DIMENSIONS IN MILLIMETRES.



**BROOK CROMPTON**

Huddersfield, HD1 3LJ  
 ENGLAND

DRG. No.	M9111
DRG. REF.	
REVISION: A	M.E DATE 14.6.02