



**131F0436**

**FC-302P37KT5E20H2XGXXXXXXXAXBXXXXDX**

Frequency converter  
 FC-302P37KT5E20H2XGXXXXXXXAXBXXXXDX  
 VLT® AutomationDrive FC-302  
 (P37K) 37 KW / 50 HP,  
 Three phase, 380 - 500 VAC, (E20) IP20 / Chassis  
 RFI Filter  
 No brake chopper  
 Graphical Loc. Cont. Panel  
 Not coated PCB, No Mains Option  
 Latest release std. SW.  
 Frame: C3  
 No A Option, No B Option  
 No C1 option, No D option

Other options according to Model code

**Model code:** FC-302P37KT5E20H2XGXXXXXXXAXBXXXXDX

The VLT® AutomationDrive represents a single drive concept that controls the entire range of operations from ordinary to servo like applications on any machine or production line.

[View Efficiency Data](#)

**PRODUCT DETAILS**

<b>Gross weight</b>		35.64 Kilogram
<b>Net weight</b>		32.79 Kilogram
<b>Volume</b>		188.19 Liter
<b>EAN</b>		5702427397316
<b>Product View (Switch)</b>	GLBL	Global (Standard)
<b>Product Group</b>	FC-	VLT® AutomationDrive FC-
<b>Series</b>	302	302
<b>Power Rating</b>	P37K	(P37K) 37 KW / 50 HP
<b>Phase</b>	T	Three phase
<b>Mains Voltage</b>	5	380 - 500 VAC
<b>Enclosure</b>	E20	(E20) IP20 / Chassis
<b>RFI Filter</b>	H2	RFI Filter
<b>Brake - Safe Stop</b>	X	No brake chopper
<b>LCP</b>	G	Graphical Loc. Cont. Panel
<b>Coating PCB</b>	X	Not coated PCB
<b>Mains Option</b>	X	No Mains Option
<b>Adaptation A</b>	X	Standard Cable Entries
<b>Adaptation B</b>	X	No adaptation
<b>Software Release</b>	SXXX	Latest release std. SW.
<b>Software Language Pack</b>	X	Standard Language Pack
<b>A Option</b>	AX	No A Option
<b>B Option</b>	BX	No B Option
<b>C0 Option MCO</b>	CX	No C0 option
<b>C1 Option</b>	X	No C1 option

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Product Detail | FC-302P37KT5E20H2XGXXXXXXXAXBXCXXXXDX

## PRODUCT DETAILS

<b>C Option Software</b>	XX	No software option
<b>D Option</b>	DX	No D option
<b>Frame Size</b>	C3	C3
<b>Typecode Part 1</b>		FC-302P37KT5E20H2XGX
<b>Typecode Part 2</b>		XXXXXXXXAXBXCXXXXDX
<b>Product Catalog</b>	NO_VIEW	NO VIEW
<b>Power 150% (HO) [KW]</b>	37	37
<b>Power 110% (NO) [KW]</b>	45	45
<b>Height [mm]</b>	550,0	550,0
<b>Width w/ no C options [mm]</b>	308,0	308,0
<b>Depth [mm]</b>	333,0	333,0
<b>Depth with Option A/B [mm]</b>	333,0	333,0
<b>kVA</b>	50.6	50.6
<b>Power Loss NO [W]</b>	843	843
<b>Power Loss NO [W]</b>	843	843
<b>Power Loss HO [W]</b>	697	697
<b>Power Loss HO [W]</b>	697	697
<b>Continuous Current (NO) [A]</b>	90	90
<b>Intermittent Current (NO) [A]</b>	99	99
<b>Continuous Current (NO) [A]</b>	80	80
<b>Intermittent Current (NO) [A]</b>	88	88
<b>Continuous Current (HO) [A]</b>	73	73
<b>Intermittent Current (HO) [A]</b>	110	110
<b>Continuous Current (HO) [A]</b>	65	65
<b>Intermittent Current (HO) [A]</b>	97.5	97.5
<b>Calculated Gross Weight [kg]</b>		35.64
<b>Calculated Net Weight [kg]</b>		32.79
<b>ECCN EU</b>	Y901	Y901
<b>ECCN US</b>	3A999.a	3A999.a
<b>Vendor</b>	ERR01	Cannot Determine Vendor
<b>Recommended Factory</b>	ERR01	Cannot Determine Vendor
<b>Modelcode01</b>		FC-302P37KT5E20H2XGX
<b>Modelcode02</b>		XXXXXXXXAXBXCXXXXDX
<b>Recommended Plant</b>	ERR01	ERR01

[For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store](#)