TECHNICAL DATA

Three Phase Electric Motors - Cast Iron Frame
UM3C 225M-4 IE3
45 kW / 60 Cv
1485 RPM



Motor type:	**UM3C 225M-4 IE3**
Output:	**45 kW / 60 Cv**
Speed (min^{-1}):	**1485 RPM**
Voltage:	**400 V**
Frequency:	**50 Hz**
Current:	**80.2 A**
Power factor (Cos Ø):	**0.86**
Poles:	**4**
Insulation class:	**F**
Temperature rise Class:	**B**
Efficiency 50%:	**93.4 %**
Efficiency 75%:	**94.6 %**
Efficiency 100%:	**94.3 %**
Torque:	**289 N.m**
Tstarting/Tnominal:	**2.0**
Istarting/Inominal:	**7.4**
Tmaximum/Tnominal:	**2.3**
Noise:	**78 Db(A)**
Weight:	**390 Kg**
Bearing DE:	**6313 C3**
Bearing NDE:	**6313 C3**

Regime - S1 **Altitude - 1000m** **Environment Temperature - 40ºC**

* References applied only in the UK

CONTACTS:

Universal Motors UK, Ltd
Unit E2, Meltham Mills Industrial Estate, Meltham Mills Road, Meltham, Holmfirth
West Yorkshire HD9 4AR, U.K

Tel: +44(0) 1484 660 222
Fax: +44(0) 1484 660 333
Mail: enquiries@universalmotors-group.co.uk

Universal Motors