


ENCLOSURE
 FRAME AND COVERS 1.2 mm THICK PREGALVANISED MILD STEEL
 NATURAL FINISH

DEGREE OF PROTECTION
 RESISTOR ENCLOSURE INGRESS (IEC 529) IP20

TECHNICAL DATA
 MAX. RATED VOLTAGE 1000 V ac or dc
 RATED CONTINUOUS POWER 6 kW
 RESISTANCE 1.5-1864 Ω AT 25°C
 MAX. TEMPERATURE RISE 600°C
 ELEMENT TYPE HP1500
 ELEMENT MATERIAL Fe-Cr-Al
 UNIT WEIGHT 5 kg

ALL INSULATOR MATERIAL IS CERAMIC

D	5513	OVERALL DIMENSION CHANGED, 380 WAS 399, MATERIAL THICKNESS CHANGED		KA	
ISSUE	ECN	DESCRIPTION	DATE	DRAWN	APPROVED
MATERIAL:			WEIGHT: N/A		
FINISH:			1st CONTRACT:		
TOLERANCE:- +/-0.5 mm (UOS) DIMENSIONS IN mm (UOS)			DRAWING TITLE		
CRESSALL Evington Valley Road, Leicester. LE5 5LZ UK. © Cressall Resistors Ltd 2011			ES4 GERNERAL ARRANGEMENT		
TEL: (+44)(0)116 273 3633 FAX: (+44)(0)116 273 7911 email: sales@cressall.com www.cressall.com			DRAWING.No.		SHEET
DRAWING STATUS: Released			118016		ISS 1 of 1 D