

DFE

Typical Applications	Light Duty	Standard Duty	Medium Duty	Heavy Duty						
	<p>Step 1 - Select the application from the list and follow that column down.</p> <p>Compressor - Unloaded Mixer - Unloaded Conveyor - Unloaded</p> <p>Do not use Light Duty when there is a possibility of the motor starting under a heavy load.</p>	<p>Agitator Compressor - Rotary Vane Compressor - Scroll Bow Thruster - Zero Pitch Fan - Low Inertia Feeder - Screw Lathe Machines Moulding Machine Plastic and Textile Machines Pump - Submersible - Centrifugal Pump - Submersible - Rotodynamic Saw - Band Transformers Voltage Regulators</p>	<p>Compressor - Centrifugal Compressor - Reciprocating Compressor - Rotary Screw Ball Mill Bow Thruster - Loaded Conveyor - Loaded Grinder Hammer Mill Mills - flour etc. Mixer - Loaded Pelletizers Press, Flywheel Positive Displacement Pump - Reciprocating Positive Displacement Pump - Rotary Pump Jack Rolling Mill Roots Blower Saw - Circular Screen - Vibrating Tumblers</p> <p>The DFE is not suitable for very high inertia loads such as centrifuges, loaded crushers or start times >30s.</p>	<p>Crusher Shredder Wood Chipper Fan - High Inertia >85A</p>						
<p>Step 2 - Confirm the rated starting capability of the soft start against the application.</p> <p>Trip Class Rated Starting Capability Max Starts per Hour</p>	<p>Trip Class 2 3x Motor Current - 5secs 10 starts/hour</p>	<p>Trip Class 10 3x Motor Current - 23secs 3.5x Motor Current - 17secs 5 starts/hour or 3 starts/hour</p>	<p>Trip Class 20 4x Motor Current - 19secs 5 starts/hour or 3 starts/hour</p>	<p>Trip Class 30 4x Motor Current - 29secs 5 starts/hour or 3 starts/hour</p>						
<p>Step 3 - Consider the operating environment and make the model selection on a higher horsepower rating.</p> <p>Height Above Sea Level Operating Temperature Increased Starts per Hour</p>	<p>Standard operating height is 1000m, for every 100m increase motor Amps/kW by 1%, up to 2000m. Example: For a 20A motor at 1500m make model selection based on 21A (5% higher)</p> <p>Standard operating temperature is 40degC, for every 1degC above, increase motor Amps/kW by 2%, up to 60degC. Example: For a 20A motor at 50degC make model selection based on 24A (20% higher)</p> <p>Use our online tool to select the model.</p>									
<p>Step 4 - Select your motor Voltage and Horsepower and select model.</p>	Motor Rating						Select Model 10 starts/hour	Select Model 5 starts/hour	Select Model 5 starts/hour	Select Model 5 starts/hour
	230V		460V		400V					
	HP	I _e (A)	HP	I _e (A)	kW	I _e (A)				
	5	15.2	10	14	7.5	15.5	DFE-02	DFE-02	DFE-04	DFE-04
	7.5	22	15	21	11	22	DFE-02	DFE-04	DFE-04	DFE-06
	10	28	20	27	15	29	DFE-04	DFE-06	DFE-06	DFE-08
	10	28	25	34	18.5	35	DFE-06	DFE-06	DFE-08	DFE-12
	15	42	30	40	22	41	DFE-06	DFE-08	DFE-12	DFE-16
	20	54	40	52	30	55	→	DFE-12	DFE-16	DFE-22
	20	54	50	65	37	66	→	DFE-14	DFE-22	DFE-22
	30	80	60	77	45	80	→	DFE-22	DFE-22	DFE-24
	30	80	75	96	55	97	→	DFE-22	DFE-24	DFE-26
	50	130	100	124	75	132	→	DFE-26	↓	↓
	3 starts/hour						3 starts/hour	3 starts/hour	3 starts/hour	3 starts/hour
	50	130	100	124	75	132	→	↓	DFE-30	DFE-32
60	154	125	156	90	160	→	→	DFE-30	DFE-32	
75	192	150	180	110	195	→	→	DFE-32	DFE-34	
75	192	200	240	132	230	→	→	DFE-34	DFE-36	
100	248	200	240	160	280	→	→	DFE-36	DFE-38	
125	312	250	302	200	350	→	→	DFE-38	-	
150	360	300	361	200	350	→	→	DFE-38	-	





SGY

	Typical Applications				Standard Duty	Medium Duty	Heavy Duty				
					Standard Duty	Medium Duty	Heavy Duty				
Step 1 - Select the application from the list and follow that column down.					Agitator Compressor - Rotary Vane Compressor - Scroll Bow Thruster - Zero Pitch Fan - Low Inertia Feeder - Screw Lathe Machines Moulding Machine Plastic and Textile Machines Pump - Submersible - Centrifugal Pump - Submersible - Rotodynamic Saw - Band Transformers Voltage Regulators	Compressor - Centrifugal Compressor - Reciprocating Compressor - Rotary Screw Ball Mill Bow Thruster - Loaded Conveyor - Loaded Grinder Hammer Mill Mills - flour etc. Mixer - Loaded Pelletizers Press, Flywheel Positive Displacement Pump - Reciprocating Positive Displacement Pump - Rotary Pump Jack Rolling Mill Roots Blower Saw - Circular Screen - Vibrating Tumblers	Crusher Shredder Wood Chipper Fan - High Inertia >85A				
Step 2 - Confirm the rated starting capability of the soft start against the application.	Trip Class Rated Starting Capability Max Starts per Hour				Trip Class 10 3x Motor Current - 23secs 3.5x Motor Current - 17secs 5 starts/hour or 3 starts/hour	Trip Class 20 4x Motor Current - 19secs 5 starts/hour or 3 starts/hour	Trip Class 30 4x Motor Current - 29secs 5 starts/hour or 3 starts/hour				
Step 3 - Consider the operating environment and make the model selection on a higher horsepower rating.	Height Above Sea Level Operating Temperature Increased Starts per Hour				Standard operating height is 1000m, for every 100m increase motor Amps/kW/HP by 1%, up to 2000m. Example: For a 100A motor at 1500m make model selection based on 105A (5% higher) Standard operating temperature is 50degC, for every 1degC above, increase motor Amps/kW/HP by 4%, up to 60degC. Example: For a 100A motor at 55degC make model selection based on 120A (20% higher) Use our online tool to select the model.						
Step 4 - Select your motor Voltage and Horsepower and select model.	Motor Rating In Line				Motor Rating In Delta				Select Model 5 starts/hour @ 50°C	Select Model 5 starts/hour @ 50°C	Select Model 5 starts/hour @ 50°C
	400V		460V		400V		460V				
	kW	I _e (A)	HP	I _e (A)	kW	I _e (A)	HP	I _e (A)			
	7.5	17	10	17	15	29	20	29	SGY-101	SGY-103	SGY-105
	11	22	15	21	18.5	38	25	36	SGY-103	SGY-105	SGY-107
	15	29	20	27	22	50	30	47	SGY-105	SGY-107	SGY-109
	18.5	35	25	34	30	61	40	59	SGY-107	SGY-109	SGY-111
	22	41	30	40	37	71	50	69	SGY-109	SGY-111	SGY-113
	30	55	40	52	45	95	60	90	SGY-111	SGY-113	SGY-115
	37	66	50	65	55	114	75	113	SGY-113	SGY-115	SGY-117
	45	80	60	77	75	139	100	133	SGY-115	SGY-117	SGY-201
	55	100	75	96	90	173	125	166	SGY-117	SGY-201	SGY-203
	75	132	100	124	110	229	150	215	SGY-201	SGY-203	SGY-205
	90	160	125	156	150	277	200	270	SGY-203	SGY-205	↓
	110	195	150	180	185	338	250	312	SGY-205	↓	↓
	3 starts/hour @ 50°C				3 starts/hour @ 50°C				3 starts/hour @ 50°C	3 starts/hour @ 50°C	3 starts/hour @ 50°C
	90	160	125	156	150	277	200	270	↓	↓	SGY-301
	110	195	150	180	185	338	250	312	↓	SGY-301	SGY-303
	132	242	200	242	220	419	350	419	SGY-301	SGY-303	SGY-305
	160	302	250	302	300	523	450	523	SGY-303	SGY-305	SGY-307
	200	361	300	361	355	625	500	625	SGY-305	SGY-307	SGY-309
	250	430	350	414	425	745	500	717	SGY-307	SGY-309	↓
	280	500	400	477	500	866	600	826	SGY-309	↓	↓
	3 starts/hour @ 40°C				3 starts/hour @ 40°C				3 starts/hour @ 40°C	3 starts/hour @ 40°C	3 starts/hour @ 40°C
250	430	350	414	425	745	500	717	↓	↓	SGY-401	
280	500	400	477	500	866	600	826	↓	SGY-401	SGY-403	
355	610	500	590	600	1057	800	1022	SGY-401	SGY-403	SGY-501	
400	722	600	722	710	1251	1000	1251	SGY-403	SGY-501	SGY-503	
500	850	700	840	850	1472	1100	1455	SGY-501	SGY-503	SGY-505	
560	960	800	960	950	1663	1250	1663	SGY-503	SGY-505	-	
630	1080	900	1080	1100	1871	1500	1871	SGY-505	-	-	