


IH 950

INCREMENTAL HOLLOW SHAFT ENCODER

Very Heavy Duty Construction
Shaft Mounted
Range of shaft bores (14 – 30 mm)
25000 PPR Maximum
4.75 to 30 Volts, RS 422 Compatible
300 kHz Maximum Frequency




ELECTRICAL SPECIFICATIONS

Supply Voltage	4.75-30 V DC
Current Consumption	40 mA (max)
Output Circuit	Push-Pull, RS 422A
Impulse Frequency	300 kHz (max)
Logic Level (high)	Vcc - 0.7 Volt
Logic Level (low)	0.25 Volt (max)
Short Circuit Protection	100 %


MECHANICAL SPECIFICATIONS

Cover	Aluminium
Body	Aluminium
Shaft	Stainless Steel
Speed	6000 RPM (max)
Torque	> 0.04 Nm
Loading	Axial 50 N, Radial 30 N
Protection	IP 65
Temperature	-20°...+70° C (-4°...+158° F) +100° C (+212° F) Optional
Weight	1.254 lb (570 g)

OUTPUT SIGNALS



A Leads B in the CW Direction (facing shaft)
Complimentary channel also available



ORDERING CODE

IH **950** - -

a b c d e f g h Pulses Per Revolution

- Note:** Special functions and designs will be designated by a 4 digit code at the end of the part number. Consult factory for further details

CONNECTIONS

☐ ☐ ☐ ☐ **31** ☐