

(Different COM ports for different cables)

Communications	Port	Protocol (DriveView)	Baud rate	Brand	Interface	Order #	S+/S-	DV Setting Protocoll	DV Setting Baud Rate
M100	RJ45	RS485	ModBus RTU	9600	"1904"	USB-Serial Port	64090354	No	
G100	RJ45	RS485	ModBus RTU	9600	"1904"	USB-Serial Port	64090354	Yes	
S100	RJ45	RS232	ModBus RTU	19200	Prolific	USB-to-Serial Comm Port	64090353	Yes	
iS7	RJ45	RS232	ModBus RTU	19200	Prolific	USB-to-Serial Comm Port	64090353	Yes	
H100	RJ45	RS232	ModBus RTU	19200	Prolific	USB-to-Serial Comm Port	64090353	Yes	
	USB	RS485	LS Inv 485	9600	LSIS	LSIS CDC Device	46310162	Yes	
L100	USB	RS485	LS Inv 485	9600	LSIS	USB-to-Serial Comm Port	64090353	Yes	

Connection Settings

Connections

Type: Modbus-RTU

Setting COM Port

Settings

Station No: 1

COM: COM7

Baudrate: 9600

Connection Settings

Connections

Type: Modbus-RTU

Setting COM Port

Settings

Station No: 1

COM: COM4

Baudrate: 19200

Connection Settings

Connections

Type: LS INV 485

Setting COM Port

Settings

Station No: 1

COM: COM5

Baudrate: 9600

Connection Settings

Connections

Type: LS INV 485

Setting COM Port

Settings

Station No: 1

COM: COM5

Baudrate: 9600