



Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhaltes sind nur mit unserer Zustimmung gestattet. Alle Rechte vorbehalten.
 Passing on as well as duplication of this document, utilization and report of their contents are permitted only with our agreement. All rights reserved.

Dimension drawing:**Mechanical Data:**

Length L	480 mm	Fixing space N1	356 mm	Weight	121 kg
		Fixing space N2	185 mm	Copper-Weight	1.9 kg
Height H	450 mm	Diameter D1	13 x 20 mm	Al-Weight	12.3 kg
Width B1	355 mm	Diameter D2	11 mm	Terminals	Cu 30 x 4 mm
Width B2	221 mm	Length A1	39 mm		

Electrical Data:

Rated current:	I rms	3 x	320 A	
linear up to:			384 A	
Voltage:	U	3 x	400 V	(50 / 60 Hz)
Inductance:	L	3 x	0.130 mH	-10 % / +10 %
DC resistance:	R	3 x	0.6 mΩ	-10 % / +10 %
Capacitance:	C	3 x	120.0 μF	
Switching freq.:	f _c		≥ 1500 Hz	
Power losses:	P		500.0 W	
Cooling class:			AN	
Thermal class:			F	@ 40 °C ambient
Climate class:			25/085/21	DIN IEC 68 Part 1
Max. winding temp:			140 °C	
Degree of protection:			IP 00	

Schematic:**Tests:**

Inductance (mH)	Lo ± 10 %	(100 Hz/1 V)
High voltage	2.5 kV / 60 s	Winding - Winding
	2.5 kV / 60 s	Winding - PE
mechan. dimensions		
Visual inspection	yes	(Packaging, Air gap, Bandage)

Label:

Designation:	CNW 933/320 S/0.13/400/50
Text 1:	REO-3ph-sinusoidal filter
I[A]	320
U[V]	400
L[mH]	0.130
Text 2:	
Terminal designation:	Start 1/3/5 End 2/4/6

Cond.	Date	Name	Amendment
	Date	Name	
signed	08.09.2015	Schaper	
revised by	13.12.2016	Schaper	
checked			

Designation:

REO-3ph-sinusoidal filter**CNW 933/320 S/0.13/400/50****Project 405100093345001**