


TEC-A B3 Foot Mounted



MS56-160 B3 Overall & Installation Dimension

160M/L	160	254	210/254	108	ø42	110	12	37	15X19	290	390	ø320	620	2-M32X1.5	64	143	143
132M/L	132	216	178	89	ø38	80	10	33	12X16	252	325	ø270	475/500	2-M25X1.5	38	112	112
132S	132	216	140	89	ø38	80	10	33	12X16	252	325	ø270	436	2-M25X1.5	38	112	112
112	112	190	140	70	ø28	60	8	24	12X16	220	292	ø230	395	2-M25X1.5	32	112	112
100	100	160	140	63	ø28	60	8	24	12X16	196	252	ø205	386	1-M20X1.5	26	105	105
90L1/L2	90	140	125	56	ø24	50	8	20	10X13	175	235	ø185	335/365	1-M20X1.5	30	105	105
90S	90	140	100	56	ø24	50	8	20	10X13	175	235	ø185	310	1-M20X1.5	30	105	105
80	80	125	100	50	ø19	40	6	15.5	10X13	160	217	ø165	290	1-M20X1.5	27	105	105
71	71	112	90	45	ø14	30	5	11	7X10	132	188	ø145	255	1-M20X1.5	20	94	94
63	63	100	80	40	ø11	23	4	8.5	7X10	120	173	ø130	215	1-M16X1.5	14	94	94
56	56	90	71	36	ø9	20	3	7.2	5.8X8.8	110	156	ø120	195	1-M16X1.5	14	88	88
FRAME	H	A	B	C	D	E	F	G	K	AA	AD	AC	L	KK	TBS	TBW	TBH