



TEC ELECTRIC MOTORS LTD

Technical Data Sheet

Model **T2A 711-2**

Housing material		Aluminum
Phase		Three
Frame size		71
Power(50Hz)	kW	0.37
Current(A)230V	Δ	1.67
Current(A)400V	Y	0.97
Speed(50Hz)	(r/min)	2820
Efficiency	IE2	
	Eff.100%	70.0
	Eff.75%	66.30
	Eff.50%	62.0
Power factor cosφ	100% load	0.79
60Hz 265/460V	Power(kW)	0.43
60Hz 276/480V	Power(kW)	0.44
Speed(60Hz)	(r/min)	3390
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	1.25
Tst/Tn (Times)	2
Tmax/Tn (Times)	2.2
Tmin/Tn (Times)	1.5
Ist/In (Times)	5
Bearings type(DE)	6202-2RZ
Bearings type(NDE)	6202-2RZ
Oil seals	15x25x7
Cable glands	1-M20*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	64
Net weight(kg)	4.90
Moment of inertia (kg*m ²)	0.000368667