



# TEC ELECTRIC MOTORS LTD

## Technical Data Sheet

### Model **T2A 802-6**

Housing material		Aluminum
Phase		Three
Frame size		80
Power(50Hz)	kW	0.55
Current(A)230V	Δ	2.77
Current(A)400V	Y	1.60
Speed(50Hz)	(r/min)	935
Efficiency	IE2	
	Eff.100%	73.10
	Eff.75%	71.60
	Eff.50%	69.70
Power factor cosφ	100% load	0.68
60Hz 265/460V	Power(kW)	0.63
60Hz 276/480V	Power(kW)	0.66
Speed(60Hz)	(r/min)	1120
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	5.62
Tst/Tn (Times)	2
Tmax/Tn (Times)	2.4
Tmin/Tn (Times)	2
Ist/In (Times)	4
Bearings type(DE)	6204-2RZ
Bearings type(NDE)	6204-2RZ
Oil seals	20x34x7
Cable glands	1-M20*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	56
Net weight(kg)	10.20
Moment of inertia (kg*m <sup>2</sup> )	0.002337586