

Product data sheet

TP⁺

Low backlash planetary gearbox



Gearbox data	
Designation: TP300S-MF2-61-0M1-2S	
Gearbox type	TP ⁺
Gearbox size	300
Design keyword	Standard
Gearbox variation	Motor attachment gearbox
Gearbox stages	2
Gearbox ratio i	61
Output design	Flange
Clamping hub diameter	48 mm
Gearbox backlash	Standard
Gearbox material number	20039990

Motor mounting parts (included in delivery)	
Incl. mounting parts for servo motor	SIEMENS AG 1FT6105-xAB7x-xxxx
Adapter plate	20029075
Gearbox bushing	20010705

Order designation
TP300S-MF2-61-0M1-2S / SIEMENS AG 1FT6105-xAB7x-xxxx

Technical specifications		
Max. output torque (Depending on the specific boundary conditions of the application)	T _{2α}	3080 Nm
Max. acceleration torque (max. 1000 cycles per hour)	T _{2B}	3080 Nm
Nominal output torque (with n _N)	T _{2N}	2070 Nm
Emergency stop torque (permitted 1000 times during the service life of the gearbox)	T _{2Not}	9008 Nm
Nominal input speed (with T _{2N} and 20°C ambient temperature) ^{a)}	n _{1N}	2400 min ⁻¹
Max. input speed	n _{1Max}	4375 min ⁻¹
Mean no load running torque (with n ₁ =2000 min ⁻¹ and 20°C gearbox temp.) ^{b)}	T ₀₁₂	2.8 Nm
Max. torsional backlash	j _t	≤ 3 arcmin
Torsional rigidity ^{b)}	C _{t21}	700 Nm/arcmin
Tilting rigidity	C _{2K}	5560 Nm/arcmin
Max. axial force ^{c)}	F _{2AMax}	33000 N
Max. tilting moment	M _{2KMax}	5900 Nm
Efficiency at full load	η	93 %
Service life (for calculation, see the Chapter "Information" in our product catalogue)	L _h	> 20000 h
Weight incl. standard adapter plate	m	58.5 kg
Operating noise (with n ₁ =2000 min ⁻¹ no load)	L _{PA}	≤ 61 dB(A)
Max. permitted housing temperature		90 °C
Ambient temperature		-15 °C to 40 °C
Lubrication		lubricated for life
Paint		Innovation blue
Protection class		IP 65
Inertia (relates to the drive)	J ₁	21.4 kgcm ²

a) For higher ambient temperatures, please reduce input speed

b) Depends on clamping hub diameter

c) Refers to center of the output shaft or flange