TECHNICAL DATA

Three Phase Electric Motors - Aluminum Frame
UM3A 132MX-6 IE3
5.5 kW / 7.5 Cv
965 RPM



Motor type:	**UM3A 132MX-6 IE3**
Output:	**5.5 kW / 7.5 Cv**
Speed (min^{-1}):	**965 RPM**
Voltage:	**400 V**
Frequency:	**50 Hz**
Current:	**12.0 A**
Power factor (Cos Ø):	**0.75**
Poles:	**6**
Insulation class:	**F**
Temperature rise Class:	**B**
Efficiency 50%:	**86.2 %**
Efficiency 75%:	**88.3 %**
Efficiency 100%:	**88.0 %**
Torque:	**54.4 N.m**
Tstarting/Tnominal:	**2.0**
Istarting/Inominal:	**7.1**
Tmaximum/Tnominal:	**2.1**
Noise:	**73 Db(A)**
Weight:	**65.0 Kg**
Bearing DE:	**6308 2Z C3**
Bearing NDE:	**6308 2Z C3**

Regime - S1 **Altitude - 1000m** **Environment Temperature - 40ºC**

* References applied only in the UK

CONTACTS:

Universal Motors UK, Ltd
Unit E2, Meltham Mills Industrial Estate, Meltham Mills Road, Meltham, Holmfirth
West Yorkshire HD9 4AR, U.K

Tel: +44(0) 1484 660 222
Fax: +44(0) 1484 660 333
Mail: enquiries@universalmotors-group.co.uk

Universal Motors