


TECHNICAL DATA

Three Phase Electric Motors - Cast Iron Frame
UMHC250M-4 IE2
55 kW / 75 Cv
1480 RPM



Motor type:	UMHC250M-4 IE2
Output:	55 kW / 75 Cv
Speed (min ⁻¹):	1480 RPM
Voltage:	400 V
Frequency:	50 Hz
Current:	99 A
Power factor (Cos ϕ):	0.86
Poles:	4
Insulation class:	F
Temperature rise Class:	B
Efficiency 50%:	93.4 %
Efficiency 75%:	94.0 %
Efficiency 100%:	93.5 %
Torque:	355 N.m
Tstarting/Tnominal:	2.2
Istarting/Inominal:	7.6
Tmaximum/Tnominal:	2.3
Noise:	79 Db(A)
Weight:	450 Kg
Bearing DE:	6314 C3
Bearing NDE:	6314 C3

Regime - S1

Altitude - 1000m

Environment Temperature - 40°C

CONTACTS:

Universal Motors UK, Ltd
Unit E2, Meltham Mills Industrial Estate, Meltham Mills Road, Meltham, Holmfirth
West Yorkshire HD9 4AR, U.K.

Tel: +44(0) 1484 660 222

Fax: +44(0) 1484 660 333

Mail: enquiries@universalmotors-group.co.uk

* References applied only in the UK