

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer	: IDS		
Product line	: W22 IE3 Three-Phase	Product code :	12862522
Frame	: 71	Locked rotor time	: 54s (cold) 30s (hot)
Output	: 0.37 kW	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S1
Frequency	: 50 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/400 V	Altitude	: 1000 m.a.s.l.
Rated current	: 1.72/0.987 A	Protection degree	: IP55
L. R. Amperes	: 8.24/4.74 A	Cooling method	: IC411 - TEFC
LRC	: 4.8	Mounting	: B5T
No load current	: 1.13/0.650 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1385 rpm	Noise level ²	: 43.0 dB(A)
Slip	: 7.67 %	Starting method	: Direct On Line
Rated torque	: 0.260 kgfm	Approx. weight ³	: 11.9 kg
Locked rotor torque	: 280 %		
Breakdown torque	: 290 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 0.0008 kgm ²		
Design	: N		
Output	50%	75%	100%
Efficiency (%)	73.0	75.0	77.3
Power Factor	0.50	0.62	0.70
		Foundation loads	
		Max. traction	: 20 kgf
		Max. compression	: 32 kgf
		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6202 ZZ	6202 ZZ
Sealing	:	Oil Seal	Oil Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	
Notes			
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.		These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.	
Rev.	Changes Summary	Performed	Checked
Performed by			
Checked by			
Date	27/06/2019		
		Page	Revision
		1 / 2	

VFD OPERATION CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : IDS

Product line : W22 IE3 Three-Phase

Product code : 12862522



Performance : 230/400 V 50 Hz 4P

Rated current : 1.72/0.987 A
 LRC : 4.8
 Rated torque : 0.260 kgfm
 Locked rotor torque : 280 %
 Breakdown torque : 290 %
 Rated speed : 1385 rpm

Moment of inertia (J) : 0.0008 kgm²
 Duty cycle : S1
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	27/06/2019			